


EZL-50

Summary Data Sheet




small module TCP/UDP/IP converter
10Base-T interface
1 serial port (TTL level)
small board size (50mm x 32mm)
firmware downloadable via TFTP
DHCP, PPPoE support
easy configuration (ezConfig)
AT command emulation support
RS422/485 interface(TXDE) support

Specifications

Power	Input Voltage	5V ±0.5V
	Current	MAX 100 mA
Dimension	50mm x 32mm	
Weight	11g	
Interface	Serial	2mm pitch 1x12 connector
	Ethernet	2mm pitch 1x12 connector
Serial	TTL level(1200bps ~ 230400bps)	
Ethernet	10Base-T	
Protocols	TCP, UDP, IP, ICMP, ARP, TELNET, DHCP, PPPoE	
Firmwares	T2S	TCP, Server mode
	COD	TCP, Client mode
	ATC	TCP, Server/Client (AT emulation)
	U2S	UDP
	firmware downloadable via ethernet using TFTP client	
Utilities	ezConfig	configuration utility
	hotflash	firmware download utility
	ezterm	socket communication test utility

System Diagram



Applications

remote monitoring systems
remote metering systems
remote fire fighting equipment systems
air circulator remote control
ATM systems
health check systems
security systems
traffic display systems
etc.

Ordering Information

EZL-50A	N/A
EZL-50R	
EZL-50R-E	RoHS compliant



Sollae Systems Co., Ltd.
<http://www.ezTCP.com>

Technical support: support@ezTCP.com
Sales : sales@ezTCP.com